

Powerful and high-quality air-conditioners that maintain the desired temperature in the room automatically, without sudden changes and high energy costs, for more efficiency and quiet operation.

## Full Inverter series

**R32**  
REFRIGERANT



- Precise temperature control - Climate Control
- Energy Efficiency Class A++
- Reliable heating up to -15 °C
- Hidden display that becomes visible when you turn on the air conditioner
- Comfort and energy saving technology DC

- Inverter
- Low noise level
- Double insulated compressor outdoor unit
- High-quality materials - plastic ABS
- Auto-Restart

## PRO Inverter series

- SEER A++ • SCOP 4.0 • GMCC-TOSHIBA compressor technology
- SILENCE mode 24 dB(A) • 2-Way draining connection
- High-Density air filter • 3D Air flow control
- All DC fan motors in&out

Model	INDOOR	ASW-H09A4/FAR3DI-EU	ASW-H12A4/FAR3DI-EU	ASW-H18B4/FAR3DI-EU	ASW-H24B4/FAR3DI-EU
	OUTDOOR	ASW-H09A4/FAR3DI-EU	ASW-H12A4/FAR3DI-EU	ASW-H18B4/FAR3DI-EU	ASW-H24B4/FAR3DI-EU
Ψυκτική Απόδοση	W	2.6(1.0-3.3)	3,6 (1,2-3,8)	5,1 (1,9-5,2)	7,0 (2,9-7,2)
	BTUs/hr	8900(3400-10300)	12300(4100-13000)	17400(6500-17800)	23900(10000-24500)
Θερμαντική Απόδοση	W	2.7(1.0-3.3)	3,7 (1,0-3,8)	5,4 (1,4-5,4)	7,3 (2,1-7,4)
	BTUs/hr	9200(3400-11300)	12600(3400-13300)	18500(4800-18500)	24900(7100-25300)
Συντελεστής Απόδοσης	SEER/SCOP	6.50/5.07 (A++/A++)	6.65/5.22 (A++/A++)	6.57/5.41 (A++/A++)	6.89/6.00 (A++/A++)
Κατανάλωση (κρύο)	W	800(100-1449)	1090 (100-1600)	1650 (210-1730)	2200 (370-2900)
Κατανάλωση (ζεστό)	W	750(240-1400)	970 (200-1350)	1500 (310-1530)	1960 (440-2300)
Ρεύμα Λειτουργίας (κρύο)	A	3,6 (0,6-6,3)	4,8 (0,6-7,1)	7,3 (1,4-7,6)	10,3 (2,2-12,7)
Ρεύμα Λειτουργίας (ζεστό)	A	3,4 (1,2-6,0)	4,3 (1,3-5,7)	7,1 (1,8-6,7)	10,5 (2,6-10,0)
Παροχή Αέρα (υψηλή)	m <sup>3</sup> /h	600	600	850	1150
Στάθμη Θορύβου Εσωτ. Μονάδας (soft/χαμ/μετρ/δυν)	dB (A)	24/34/37/40	25/35/38/41	30/39/42/45	35/44/47/50
Στάθμη Θορύβου Εξωτ. Μονάδας	dB (A)	51	51	55	60
Διαστάσεις Εσωτ. Μονάδας (ΜxΠxΥ)	mm	750X285X200	750X285X200	900X310X225	1082X330X233
Διαστάσεις Εξωτ. Μονάδας (ΜxΠxΥ)	mm	720x540x260	720x540x260	800x545x315	890x320x670
Βάρος Εσωτ. Μονάδας	kg	7,5	8	12,0	14,0
Βάρος Εξωτ. Μονάδας	kg	26,0	26,0	35,0	45,0
Σωλήνες Αερίου	liquid mm	1/4"	1/4"	1/4"	1/4"
	gas mm	3/8"	3/8"	1/2"	5/8"